

Machine construction

Size 1:

Overall dimensions: approx. 3100 x 1500 x 1000 mm
Dimensions inside the frame: approx. 2880 x 1280 mm

Size 2:

Overall dimensions: approx. 4100 x 1760 x 1000 mm
Dimensions inside the frame: approx. 3880 x 1540 mm

Size 3:

Overall dimensions: approx. 4100 x 2000 x 1000 mm
Dimensions inside the frame: approx. 3880 x 1780 mm

- The upmarket Columbus machines are the result of decades long, market driven research and development. They were created by and for practitioners and perfected together with operators and manufacturers of materials.
- The massive welded steel construction is 100 % torsionally rigid and resistant against bending, even when processing big work pieces. The results are longevity and production safety in any situation.
- The ergonomic and smooth-running operation ensures an absolutely body-friendly working method even during fast production processes, what minimizes downtime and ensures fatigue-free working.

Membrane

Natural rubber membrane

Material: natural rubber NR
Dimensions: 3100 x 1500 / 4100 x 1800 / 4100 x 2000 x 2 mm
Heat resistance: up to + 130 °C
Elongation at tear: 600 %
Material hardness: 40 Shore-A
Colour: grey

Silicone membrane economy

Material: silicone
Dimensions: 3100 x 1500 / 4100 x 1800 / 4100 x 2000 x 2 mm
Heat resistance: up to + 230 °C
Elongation at tear: 700 %
Material hardness: 40 Shore-A
Colour: white/transparent

Silicone membrane high-performance

Material: silicone
Dimensions: 3100 x 1500 / 4100 x 1800 / 4100 x 2000 x 2 mm
Heat resistance: up to + 230 °C
Elongation at tear: 700 %
Material hardness: 40 Shore-A
Colour: transparent

- Columbus membranes are extremely heat resistant and very resilient against abrasion, this minimizes expenses on wearing parts.
- They have extraordinary elasticity and rebound capabilities and guarantee best pressing results for a long time.
- Depending on the required heat resistance and mechanical load, Columbus membranes are available in different material types and quality categories (natural rubber, silicone economy, silicone high-performance). Thus, there is always the ideal equipment at the best price for every application.

Membrane fast-change system

Every membrane is suitable
Incl. fixing bolts and profiles

- With the unique Columbus membrane fast-change system, a membrane change can be carried out in less than 10 minutes, what optimizes production processes and significantly shortens production times.
- The sturdy steel frame guarantees a vacuum-tight membrane attachment and thus ensures the best press results and production safety.

Phenolic resin working surface

Material: phenolic resin laminated plywood
Heat resistance: up to + 160 °C
Suction points: up to 70

- The Columbus working surfaces consist of a very heat-resistant and robust phenolic resin laminated plywood. These guarantee longevity even with the toughest use.
- The integrated air suction channels in the working surface, with up to 70 suction points, facilitate full ventilation and evacuation. With this system, maloperation by incorrect placed work pieces is impossible, what minimizes reject rates. Furthermore, the Air suction speed increases through that and an evenly spread pressure is guaranteed.

Vacuum pump

25 m³ high-performance vacuum pump

Type: dry running rotary vane pump
Air suction speed: 25 m³/h
Pressure: up to 9 t/m²

40 m³ high-performance vacuum pump

Type: dry running rotary vane pump

- The high-performance vacuum pumps from Columbus are 100 % oil-free. While conventional oil-lubricated vacuum pumps spread their lubricating oil throughout the entire room as a harmful and surface-contaminating oil mist, Columbus dry-running rotary vane pumps ensure clean and safe production facilities for people, materials and environment.
- Depending on the requirements and the size of the machine, Columbus

Air suction speed: 40 m³/h

Pressure: up to 9 t/m

80 m³ high-performance vacuum pump

Type: dry running rotary vane pump

Air suction speed 80 m³/h

Pressure: up to 9 t/m²

offers a variety of high-performance vacuum pumps with different Air suction speed. Thus, there is always the ideal equipment at the best price for every demand.

- High-performance vacuum pumps from Columbus are maintenance-free. This means no expense for servicing - neither time nor cost.

Control unit

Switch for pump on/off

Vacuum control lever for vacuum generation and reduction

Pressure monitoring: analogue vacuum pressure gauge

- Vacuum generation and vacuum reduction are controlled via a vacuum control lever, which is placed centrally on the machine.
- The vacuum pressure is monitored via a precise analogue vacuum pressure gauge in bar relative.
- Thanks to the central and clear provision of all control and monitoring elements, the production process can be extremely speeded up and optimally monitored.

Vacuum pressure control

Mechanical vacuum pressure regulator

Control range of vacuum pressure: 200 - 900 mbar rel.

Digital FESTO vacuum pressure control

Control range of vacuum pressure: precisely 20 - 900 mbar rel. (variable)

incl. 200 / 500 l vacuum tank

- With a vacuum pressure control, the vacuum pressure of the vacuum press can be adjusted variably. Since the processing of certain materials (e.g. very soft materials) requires an adapted vacuum pressure, new, profitable application possibilities are opened up with a vacuum pressure control.
- The vacuum pressure can be controlled with either a mechanical regulator, or a digital controller.
- The digital vacuum pressure control is available in combination with a 200 / 500 l vacuum tank, which enables an extremely fast vacuum generation. Due to the faster vacuum generation, materials and adhesives can be processed with very short process times.

Heating hood economy

Type: Tubular heating elements

Tubular heating elements: 3 pcs.

Heating power: 5.4 kW

Thermostat: variable 0 - 80 °C

- The heating hood economy consists of a very sturdy and robust aluminium construction that guarantees longevity and production safety even with the toughest use.
- Inside the heating hood there is a high-performance and energy-efficient heating system, consisting of tubular heating elements, which is designed for continuous operation and long periods of heating.
- Due to the additional use of heat, cycle times can be extremely shortened, which results in higher productivity.
- The low weight of the sturdy aluminium construction allows easy opening and closing of the heating hood, resulting in an efficient and less exhausting operation, which raises productivity and minimizes downtimes.
- The thermostat is variably adjustable from 0 - 80 °C and thus sets no limits in the temperature selection.

Vertical opening mechanism

Type: pneumatic

Pneumatic cylinder: 8 pcs.

two-hand safety operation

VACUPLUS, Size 1:

Overall dimensions: approx. 3400 x 1560 x 1400/1900 mm

Stroke: approx. 850 mm

VACUPLUS, Size 2:

Overall dimensions: approx. 4400 x 1820 x 1400/1900 mm

Stroke: approx. 1000 mm

VACUPLUS, Size 3:

Overall dimensions: approx. 4400 x 2060 x 1400/1900 mm

Stroke: approx. 1000 mm

- The vertical, pneumatic opening mechanism guarantees precise pressing of different shapes and geometries, since the vertical travel does not cause any shifting of the layers and the base stencil. This level of precision reduces reject rates to zero.
- The possibility of a 4-sided operation of the vacuum press ensures an uncomplicated and fast workflow and increases productivity.
- The reliable, oil-free pneumatic cylinders protect work pieces and the production facility against oil contamination.
- The built-in two-hand safety operation guarantees maximum safety.

Easy opening

Pneumatic cylinders: 2 pcs.

- The "Easy opening" feature makes opening and closing the clam shell opening even easier. The result is a more comfortable way of working and a speeded-up production process.